



EMRx Onshore

The Online Electronics EMRx Onshore receiver is a robust, state of the art, multi-frequency, electromagnetic (EM) receiver used for locating lost or stalled pigs and tracking pigs fitted with any EM pig transmitters. It can also be used to confirm a pig has left or arrived at a particular location and for general monitoring of pig movements.

Key benefits:

- Has the potential to greatly reduce downtime, and therefore costs, by facilitating the process of locating a stalled pig or confirming if a pig has left the launcher or been successfully received.
- The enhanced sensitivity permits the location of transmitters even within very heavy walled receivers/launchers, pipeline bundles or Pipe-in-Pipe.
- Detection through pipeline walls in excess of 40mm is possible dependent on transmitter settings and environmental factors.
- Multi-frequency feature allows user to identify and locate individual pigs.
- Digital Signal Processing (DSP) allows use in high noise environments with more reliable signal acquisition.
- Intuitive and easy to use - one control on the unit carries out all functions.
- The EMRx Onshore shares common features and functionality with the EMRx Subsea ensuring a smooth and simple transition between the two units.

Royal Mechanical Group Pty Ltd
+ 61 (0) 452 506 896
Sales@royalmechgroup.com

www.royalmechgroup.com

Online Electronics Limited
+ 44 (0)1224 714 714
OEL-Sales@ik-worldwide.com

online-electronics.com




The EMRx unit provides three colour coded (red, blue and white) 20x LED bargraphs which can be individually configured in the field via Bluetooth using OEL's EMRx Applications to display received signal at any fixed frequency between 10Hz and 30Hz.

The EMRx Applications can allow advanced receiver functionality such as tracking six colour coded frequencies, an audio output and the ability to mark a point of interest on the signal chart along with any relevant notes that can be reviewed at a later date.

Specification

Typical Lifetime used continuously with Bluetooth	30 hours
Typical Lifetime used continuously without Bluetooth	100 hours
Battery Type	6x 1.5V, Alkaline, AA Cells
Frequency Range	10Hz to 30Hz
Operating Temperature Range	-20°C to +50°C (-4°F to 122°F)
Length	369mm (14.5")
Width	92mm (3.6")
Weight	1.8kg (4.0lbs)
Housing Material	Polycarbonate
Endcap Material	Acetal
Bumper Material	EPDM Rubber



EMRx application Signal Chart displaying a 22Hz transmitter pulsing once every 2 seconds and a 17Hz transmitter pulsing once every 5 seconds.



ROYAL
OIL & GAS

Collaborate • Innovate • Succeed

OEL
CHALLENGE
ACCEPTED